

In the Claims:

This listing of claims will replace all prior listing of claims in the application.

Listing of Claims:

1. – 15. (Cancelled)

16. (Currently amended) The stage lighting system of ~~claim 7~~ claim 18, wherein the light control system comprises two independent circuits, and wherein each of the two independent circuits is coupled to alternating ones of the plurality of light sources.

17. (Original) The stage lighting system of claim 16, wherein the light control system comprises independent switches coupled to each of the plurality of light sources.

18. (Currently amended) A stage lighting system for illumination of a stage with soft light, the system comprising:

- a rectangular frame having a series of light bars positioned therein;
- a plurality of globes disposed along the light bars;
- a reflective surface on the rectangular frame behind the plurality of globes;
- a diffusion layer on the rectangular frame in front of the plurality of globes;
- at least one eggcrate louver on the diffusion layer;
- a mobile support attached to the rectangular frame that enables the rectangular frame to be moved along a surface; ~~and~~
- a light control system configured to regulate electrical power to the plurality of globes, such that an illumination intensity of individual ones of the plurality of globes can be varied; and
- an eggcrate louver frame supporting the eggcrate louver;
- a diffusion frame supporting the diffusion layer;
- a first fastening device attached to the rectangular frame and a second fastening device attached to the eggcrate louver frame.

wherein the second fastening device engages the first fastening device to position the diffusion frame between the eggcrate louver frame and the rectangular frame.

19. (Original) The stage lighting system of claim 18 further comprising a diffusion frame positioned on the rectangular frame, wherein the diffusion frame is configured to hold at least two diffusion layers.

20. (Cancelled)

21. (Original) The stage lighting system of claim 18, wherein the rectangular frame has a length dimension that is approximately twice the height dimension.

22. (Original) The stage lighting system of claim 21, wherein the series of light bars comprises eight light bars vertically positioned in the rectangular frame, and wherein the plurality of globes are evenly disposed on the series of light bars.

23. (Original) The stage lighting system of claim 22, wherein the plurality of globes comprises thirty two globes in which four globes are evenly spaced along each of the eight light bars.

24. (Original) The stage lighting system of claim 18, wherein each of the plurality of globes comprise a tungsten light source and a light reflector positioned in proximity to the light source and configured to reflect light toward the diffusion layer.

25. (Original) The stage lighting system of claim 18, wherein the reflective surface comprises a panel having a light-reflective inner surface covering a back side of rectangular frame.

26. (Currently amended) The stage lighting system of claim 18, wherein the light control system is arranged such that an illumination intensity of alternating ones of the plurality of globes ~~can be~~ is changed.

27. (Original) The stage lighting system of claim 18, wherein the light control system is configured such that a color temperature of the illumination from the stage lighting system remains substantially constant when the total light output is reduced.